





Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

## SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** 490000750 - HOOF AND GLUSHU CLEANER ACETON FREE  
750 ML
- Other means of identification:**
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Animal care product: Cleaning agent for horse hoof. For professional users only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
Glue-U Adhesives B.V.  
Droogdokkeneiland 8  
5026 SR Tilburg - The Netherlands  
Phone: +31 (0)13 545 31 18  
info@glue-u.com  
www.glue-u.com
- 1.4 Emergency phone number:** +31 (0)6 24533395 Mon-Fri 08-17

## SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- NFPA:**  
Health Hazards: 1  
Flammability Hazards: 4  
Instability Hazards: 0  
Special Hazards: Not applicable (N/A)
- 29 CFR 1910.1200:**  
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.  
Aerosol 1: Flammable aerosols, Category 1, H222  
Press. Gas: Pressure Gases, H280  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- NFPA:**
- 
- 29 CFR 1910.1200:**  
Danger
- 
- Hazard statements:**  
Aerosol 1: H222 - Extremely flammable aerosol.  
Press. Gas: H280 - Contains gas under pressure, may explode if heated.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Substances that contribute to the classification**



Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

**SECTION 2: HAZARD(S) IDENTIFICATION (continued)**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Additional labeling:**

Keep out of the reach of children

FEDERAL HAZARDOUS SUBSTANCES ACT REGULATIONS (§1500.130 Self-pressurized containers: labeling):

Warning—contents under pressure.

Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F. Keep out of the reach of children.

**2.3 Hazards not otherwise classified (HNOC):**

Not applicable (N/A)

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:**

**Chemical description:** Aromatic Hydrocarbons

**Components:**

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: Non-applicable	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	75 - <100 %
CAS: 74-98-6	Propane	5 - <10 %
CAS: 106-97-8	Butane	5 - <10 %
CAS: 75-28-5	Isobutane	5 - <10 %
CAS: 124-38-9	Carbon dioxide	2,5 - <5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST-AID MEASURES**

**4.1 Description of necessary measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**


Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.



Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

#### SECTION 4: FIRST-AID MEASURES (continued)

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Not applicable (N/A)

#### SECTION 5: FIRE-FIGHTING MEASURES

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.



**SECTION 7: HANDLING AND STORAGE (continued)**

**B.- Technical recommendations for the prevention of fires and explosions**

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Technical measures for storage**

- Minimum Temp.: 50 °F
- Maximum Temp.: 95 °F
- Maximum time: 60 Months

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	1000 ppm	1800 mg/m³
Propane CAS: 74-98-6	Ceiling Values - TWA PEL		
Carbon dioxide CAS: 124-38-9	8-hour TWA PEL	5000 ppm	9000 mg/m³
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	5000 ppm	
Carbon dioxide CAS: 124-38-9	TLV-STEL	15000 ppm	
Butane CAS: 106-97-8	TLV-TWA		
	TLV-STEL	1000 ppm	
Isobutane CAS: 75-28-5	TLV-TWA		
	TLV-STEL	1000 ppm	

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
	PEL	1000 ppm	1800 mg/m³
Propane CAS: 74-98-6	STEL		
Carbon dioxide CAS: 124-38-9	PEL	5000 ppm	9000 mg/m³
	STEL	30000 ppm	54000 mg/m³
Butane CAS: 106-97-8	PEL	800 ppm	1900 mg/m³
	STEL		

**8.2 Appropriate engineering controls:**


A.- Individual protection measures, such as personal protective equipment




**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

**B.- Respiratory protection**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: A2)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR).

**C.- Specific protection for the hands**



Pictogram	PPE	Remarks
 Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional /industrial users, we recommend using chemical protection gloves. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

**E.- Bodily protection**

Pictogram	PPE	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**40 CFR Part 59 (VOC):**

V.O.C.(weight-percent):                      95 % weight  
V.O.C. at 68 °F:                                      703 kg/m<sup>3</sup> (703 g/L)

**California Air Resources Board (CARB) - VOC Regulatory:**



Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

V.O.C.(weight-percent):	95 % weight
V.O.C. at 68 °F:	703 kg/m <sup>3</sup> (703 g/L)
<b>South Coast Air Quality Management District (AQMD) - VOC Regulatory:</b>	
V.O.C.(weight-percent):	95 % weight
V.O.C. at 68 °F:	703 kg/m <sup>3</sup> (703 g/L)
<b>Ozone Transport Commission (OTC) Rules - VOC Regulatory:</b>	
V.O.C.(weight-percent):	95 % weight
V.O.C. at 68 °F:	703 kg/m <sup>3</sup> (703 g/L)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 68 °F:	Aerosol
Appearance:	Colorless
Color:	Colorless
Odor:	Not available
Odour threshold:	Not applicable (N/A) *

**Volatility:**

Boiling point at atmospheric pressure:	>203 °F (Propellant)
Vapour pressure at 68 °F:	4390 Pa
Vapour pressure at 122 °F:	15190 Pa (15.19 kPa)
Evaporation rate at 68 °F:	Not applicable (N/A) *

**Product description:**

Density at 68 °F:	740 kg/m <sup>3</sup>
Relative density at 68 °F:	<0.74
Dynamic viscosity at 68 °F:	0.5 cP
Kinematic viscosity at 68 °F:	67 mm <sup>2</sup> /s
Kinematic viscosity at 104 °F:	Not applicable (N/A) *
Concentration:	Not applicable (N/A) *
pH:	Not applicable (N/A) *
Vapour density at 68 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 68 °F:	Not applicable (N/A) *
Solubility in water at 68 °F:	Not applicable (N/A) *
Solubility properties:	Not applicable (N/A) *
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *
Recipient pressure:	Not applicable (N/A) *

**Flammability:**

Flash Point:	Non-applicable
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	392 °F (Propellant)
Lower flammability limit:	0.6 % Volume
Upper flammability limit:	8 % Volume

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

### Particle characteristics:

Median equivalent diameter: Non-applicable

### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties: Not applicable (N/A) \*

Oxidising properties: Not applicable (N/A) \*

Corrosive to metals: Not applicable (N/A) \*

Heat of combustion: Not applicable (N/A) \*

Aerosols-total percentage (by mass) of flammable components: Not applicable (N/A) \*

#### Other safety characteristics:

Surface tension at 68 °F: Not applicable (N/A) \*

Refraction index: Not applicable (N/A) \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):





Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Not applicable (N/A)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:
 

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:
 

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not applicable (N/A)

**Specific toxicology information on the substances:**

Identification		Acute toxicity	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable	LD50 oral	5840 mg/kg	Rat
	LD50 dermal	2920 mg/kg	Rat
	LC50 inhalation	>20 mg/L	
Carbon dioxide CAS: 124-38-9	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Propane CAS: 74-98-6	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Butane CAS: 106-97-8	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutane CAS: 75-28-5	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

**Acute Toxicity Estimate (ATE mix):**

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>5000 mg/kg (Calculation method)	Non-applicable

- CONTINUED ON NEXT PAGE -





Printing: 10/1/2024 Date of compilation: 10/31/2023 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration	Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable	LC50 5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 Not applicable (N/A)		
	EC50 Not applicable (N/A)		

Chronic toxicity:

Identification	Concentration	Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable	NOEC Not applicable (N/A)		
	NOEC 0.17 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability	Biodegradability
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable	BOD5 Not applicable (N/A)	Concentration Not applicable (N/A)
	COD Not applicable (N/A)	Period 28 days
	BOD5/COD Not applicable (N/A)	% Biodegradable 98 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential
Propane CAS: 74-98-6	BCF 13
	Pow Log 2.86
	Potential Low
Butane CAS: 106-97-8	BCF 33
	Pow Log 2.89
	Potential Moderate
Isobutane CAS: 75-28-5	BCF 27
	Pow Log 2.76
	Potential Low

12.4 Mobility in soil:

Identification	Absorption/desorption	Volatility
Propane CAS: 74-98-6	Koc 460	Henry 71636.78 Pa·m <sup>3</sup> /mol
	Conclusion Moderate	Dry soil Yes
	Surface tension 7.02E-3 N/m (77 °F)	Moist soil Yes
Carbon dioxide CAS: 124-38-9	Koc Not applicable (N/A)	Henry Not applicable (N/A)
	Conclusion Not applicable (N/A)	Dry soil Not applicable (N/A)
	Surface tension 5.7E-4 N/m (77 °F)	Moist soil Not applicable (N/A)
Butane CAS: 106-97-8	Koc 900	Henry 96258.75 Pa·m <sup>3</sup> /mol
	Conclusion Low	Dry soil Yes
	Surface tension 1.187E-2 N/m (77 °F)	Moist soil Yes
Isobutane CAS: 75-28-5	Koc 35	Henry 120576.75 Pa·m <sup>3</sup> /mol
	Conclusion Very High	Dry soil Yes
	Surface tension 9.84E-3 N/m (77 °F)	Moist soil Yes



Printing: 10/1/2024      Date of compilation: 10/31/2023      Version: 1

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

Standards for universal waste management (Title 40 of the Code of Federal Regulations (CFR) in part 273) could apply to the unused Aerosol can if it becomes a waste material.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2
- Labels: 2.1
- 14.4 Packing group, if applicable:** N/A
- 14.5 Marine pollutant:** Yes

**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Physico-Chemical properties: see section 9

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



**490000750 - HOOF AND GLUSHU CLEANER ACETON FREE  
750 ML**

Printing: 10/1/2024

Date of compilation: 10/31/2023

Version: 1

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group, if applicable:** N/A
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Special regulations: 63, 959, 190, 277, 327, 344  
EmS Codes: F-D, S-U  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
Segregation group: Not applicable (N/A)
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2023:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group, if applicable:** N/A
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations specific for the product in question:**

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *Carbon dioxide (124-38-9) ; Butane (106-97-8)*
  - California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Not applicable (N/A)
  - California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Not applicable (N/A)
  - CANADA-Domestic Substances List (DSL): *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
  - Hazardous Air Pollutants (Clean Air Act): Not applicable (N/A)
  - Massachusetts RTK - Substance List: *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - Minnesota - Hazardous substances ERTK: *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - New Jersey Worker and Community Right-to-Know Act: *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - New York RTK - Substance list: *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - NTP (National Toxicology Program): Not applicable (N/A)
  - OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
  - Pennsylvania Worker and Community Right-to-Know Law: *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - Rhode Island - Hazardous substances RTK: Not applicable (N/A)
  - The Toxic Substances Control Act (TSCA) : *Propane (74-98-6) ; Carbon dioxide (124-38-9) ; Butane (106-97-8) ; Isobutane (75-28-5)*
  - Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Not applicable (N/A)

**Specific provisions in terms of protecting people or the environment:**



**490000750 - HOOF AND GLUSHU CLEANER ACETON FREE  
750 ML**

Printing: 10/1/2024      Date of compilation: 10/31/2023      Version: 1

**SECTION 15: REGULATORY INFORMATION (continued)**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

Take into consideration other applicable federal, state, and local laws and local regulations.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

**Texts of the legislative phrases mentioned in section 2:**

- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H280: Contains gas under pressure, may explode if heated.
- H222: Extremely flammable aerosol.

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol-water partition coefficient
- Koc: Partition coefficient of organic carbon
- IARC: International Agency for Research on Cancer

Date of compilation: 10/31/2023

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET