


490101150 - GLUSHU QUICK PREFIX ADHESIVE 150 ML



Printing:	01/10/2024 Date of compilation: 31/10/2023 Version: 1
SECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: 490101150 - GLUSHU QUICK PREFIX ADHESIVE
	150 ML
	Other means of identification:
1.2	Relevant identified uses of the substance or mixture and uses advised against:
1.2	Relevant uses: Animal care product: Hoof glue. For professional users only.
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
1.0	Glue-U Adhesives B.V.
	Droogdokkeneiland 8
	5026 SR Tilburg - The Netherlands Phone: +31 (0)13 545 31 18
	info@glue-u.com
1.4	www.glue-u.com
1.4	Emergency telephone number: Medical Toxicology Unit, +44 20 7188 7188
0507	
SEC	TION 2: HAZARDS IDENTIFICATION
2.1	Classification of the substance or mixture:
	GB CLP Regulation:
	Classification of this product has been carried out in accordance with GB CLP Regulation.
	Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315
	STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
2.2	Label elements:
	GB CLP Regulation: Warning
	Hazard statements:
	Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Irrit. 2: H315 - Causes skin irritation.
	STOT SE 3: H335 - May cause respiratory irritation.
	Precautionary statements:
	P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of soap and water.
	P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+P233: Store in a well-ventilated place. Keep container tightly closed.
	P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.
	Supplementary information:
	EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
	Substances that contribute to the classification
	ethyl 2-cyanoacrylate
2.3	Other hazards:
	Product fails to meet PBT/vPvB criteria
<u> </u>	
SECT	TION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1	Substance:
	Non-applicable





490101150 - GLUSHU QUICK PREFIX ADHESIVE

150 ML



Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1

Mi	Mixture:						
Ch	Chemical description: Polyurethane resin						
Co	Components:						
In	accordance with Anne	ex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:					
	Identification	Chemical name/Classification	Concentration				
C/	CAS: 7085-85-0 ethyl 2-cyanoacrylate Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning 00 - <100 %						

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...). Additional provisions:



490101150 - GLUSHU QUICK PREFIX ADHESIVE



150 ML

Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1

SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 **Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

72 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C
Maximum time:	6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



490101150 - GLUSHU QUICK PREFIX ADHESIVE 150 ML



Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Оссира	ational exposure lir	nits
ethyl 2-cyanoacrylate	WEL (8h)		
CAS: 7085-85-0	WEL (15 min)	0.3 ppm	1.5 mg/m ³

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
ethyl 2-cyanoacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7085-85-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 230-391-5	Inhalation	9.25 mg/m³	9.25 mg/m³	9.25 mg/m ³	9.25 mg/m³

DNEL (General population):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
ethyl 2-cyanoacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7085-85-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 230-391-5	Inhalation	9.25 mg/m ³	9.25 mg/m ³	9.25 mg/m ³	9.25 mg/m ³
PNEC:					

Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

	Pictogram	PPE	Remarks
	Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
C	Specific protection	for the hands	
	Dista ana an	BBE	Demode

Pictogram	FFE	Remains
Mandatory hand	Protective gloves against minor risks (Material: Nitrile, Breakthrough time: > 30 min, Thickness: 0.38 mm)	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection		



Printing: 01/10/2024

Safety data sheet According to UK REACH

490101150 - GLUSHU QUICK PREFIX ADHESIVE 150 ML

Version: 1



Date of compilation: 31/10/2023

	Pictogram	Pictogram PPE Remarks					
	Work clothing			to the product for professional accordance with the regulations in	deterioration. For periods of prolonged exposure al/industrial users CE III is recommended, in 0 EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 3:2013, EN 464:1994.		
	Anti-slip work shoes			to the product for professiona	deterioration. For periods of prolonged exposure al/industrial users CE III is recommended, in ns in EN ISO 20345:2012 y EN 13832-1:2007		
	F Additional emerge	ency measures		1			
	Emergency measure Standards			Emergency measure	Standards		
	Emergency sho		ANSI Z358-1 64-1:2011, ISO 3864-4:20	11 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011		
	Environmental expo	sure controls:					
	spillage of both the p	roduct and its conta c Compounds in F	ainer. For additional in	nformation see subsection 7. d Vehicle Refinishing Prod			
SEC	TION 9: PHYSICAL		AL PROPERTIES				
9.1	Information on basi	c physical and ch	emical properties:				
	For complete information	ation see the produc	ct datasheet.				
	Appearance:						
	Physical state at 20 °	C:	Liqu	id			
	Physical state at 20 ° Appearance:	C:		id available			
		C:	Not				
	Appearance:	C:	Not a Colo Cha	available urless racteristic			
	Appearance: Colour: Odour: Odour threshold:	C:	Not a Colo Cha	available urless			
	Appearance: Colour: Odour: Odour threshold: Volatility:		Colo Chai Non-	available urless racteristic -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos	spheric pressure:	Not a Colo Chai Non-	available urless racteristic applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos Vapour pressure at 2	spheric pressure: 5 ºC:	Not Colo Chai Non >149 <699	available urless racteristic applicable * 9 °C 994 Pa			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 5	spheric pressure: 5 °C: 0 °C:	Not a Colo Char Non- >145 <699 Non-	available urless racteristic -applicable * 0 °C 094 Pa -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2	spheric pressure: 5 °C: 0 °C: 5 °C:	Not a Colo Char Non- >145 <699 Non-	available urless racteristic applicable * 9 °C 994 Pa			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2 Product description	spheric pressure: 5 °C: 0 °C: 5 °C:	Not a Colo Chai Non- >145 <695 Non- Non-	available urless racteristic -applicable * 0 °C 094 Pa -applicable * -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2 Product description Density at 25 °C:	spheric pressure: 5 °C: 0 °C: 5 °C: 5 °C:	Not a Colo Chai Non- >149 Non- Non- Non- Non- Non-	available urless racteristic -applicable * -applicable * -applicable * -applicable * -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2 Product description Density at 25 °C: Relative density at 25	spheric pressure: 5 °C: 0 °C: 5 °C: 5 °C: .:	Not : Colo Chai Non- >149 <699 Non- Non- 1082 1.08	available urless racteristic -applicable * -applicable * -applicable * -applicable * 2 kg/m ³			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at	spheric pressure: 5 °C: 0 °C: 5 °C: .: 5 °C: 25 °C:	Not : Colo Chai Non: >149 Non: Non: 1082 1.08 Non:	available urless racteristic -applicable * -applicable * -applicable * -applicable * 2 kg/m ³ 2 -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 2 Evaporation rate at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at Kinematic viscosity at	spheric pressure: 5 °C: 0 °C: 5 °C: 1: 5 °C: 25 °C: 25 °C: t 25 °C:	Not 2 Colo Chai Non: >149 Non: Non: 1082 1.08 Non: 1082 1.08 Non: 170	available urless racteristic -applicable * -applicable * -applicable * -applicable * 2 kg/m ³ 2 -applicable * mm ² /s			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 5 Evaporation rate at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at Kinematic viscosity at	spheric pressure: 5 °C: 0 °C: 5 °C: 1: 5 °C: 25 °C: 25 °C: t 25 °C:	Not : Colo Chai Non >149 <699 Non- Non- 1082 1.08 Non- 170 Non-	available urless racteristic -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmose Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration:	spheric pressure: 5 °C: 0 °C: 5 °C: 1: 5 °C: 25 °C: 25 °C: t 25 °C:	Not a Colo Chai Non- >149 Non- Non- 1082 1.08 Non- 170 Non- Non- 170	available urless racteristic -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmost Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Evaporation rate at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration: pH:	spheric pressure: 5 °C: 0 °C: 5 °C: 25 °C: 25 °C: t 25 °C: t 25 °C: t 40 °C:	Not : Colo Chai Non: >149 <699 Non: Non: 1082 1.08 Non: 170 Non: Non: Non:	available urless racteristic applicable * 0 °C 094 Pa applicable * applicable * 2 kg/m ³ 2 applicable * applicable * applicable * applicable * applicable *			
	Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmose Vapour pressure at 2 Vapour pressure at 2 Vapour pressure at 2 Product description Density at 25 °C: Relative density at 25 Dynamic viscosity at Kinematic viscosity at Kinematic viscosity at Concentration:	spheric pressure: 5 °C: 0 °C: 5 °C: 25 °C: 25 °C: t 25 °C: t 40 °C:	Not : Colo Chai Non- >149 <699 Non- Non- 1082 1.08 Non- 170 Non- Non- Non- Non- Non- Non- Non-	available urless racteristic -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable * -applicable *			

- CONTINUED ON NEXT PAGE -



490101150 - GLUSHU QUICK PREFIX ADHESIVE



150 ML

Printing: 01/10/2024	4 Date of compilation: 31/10/2023	Version: 1
SECTION 9: F	PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
Solubility	in water at 25 °C:	Non-applicable *
Solubility	properties:	Non-applicable *
Decompo	sition temperature:	Non-applicable *
Melting p	pint/freezing point:	Non-applicable *
Flammat	ility:	
Flash Poi	nt:	80 - 93 °C
Flammab	ility (solid, gas):	Non-applicable *
Autoigniti	on temperature:	450 °C
Lower fla	mmability limit:	Non-applicable *
Upper fla	mmability limit:	Non-applicable *
Particle of	characteristics:	
Median e	quivalent diameter:	Non-applicable
9.2 Other inf	ormation:	
Informati	on with regard to physical hazard classes	S:
Explosive	properties:	Non-applicable *
Oxidising	properties:	Non-applicable *
Corrosive	to metals:	Non-applicable *
Heat of co	ombustion:	Non-applicable *
Aerosols- compone	total percentage (by mass) of flammable nts:	Non-applicable *
Other sa	fety characteristics:	
Surface to	ension at 25 °C:	Non-applicable *
Refraction	n index:	Non-applicable *
*Not releva	nt due to the nature of the product, not providing inform	nation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:


Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
10.5	Incompatible materials:				
	Acids	Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION





490101150 - GLUSHU QUICK PREFIX ADHESIVE 150 ML



Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as
 - it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as
 - hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable


Specific toxicology information on the substances:

Identification	Acu	Acute toxicity	
ethyl 2-cyanoacrylate	LD50 oral	>5000 mg/kg	
CAS: 7085-85-0	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Acute Toxicity Estimate (ATE mix):			

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity		
	Oral	>5000 mg/kg (Calculation method)	Non-applicable	
	Dermal	>5000 mg/kg (Calculation method)	Non-applicable	

- CONTINUED ON NEXT PAGE -





490101150 - GLUSHU QUICK PREFIX ADHESIVE



150 ML

Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1 SECTION 11: TOXICOLOGICAL INFORMATION (continued) Inhalation >20 mg/L (4 h) (Calculation method) Non-applicable SECTION 12: ECOLOGICAL INFORMATION The experimental information related to the eco-toxicological properties of the product itself is not available 12.1 Toxicity: Not available 12.2 Persistence and degradability: Not available 12.3 Bioaccumulative potential: Not available 12.4 Mobility in soil: Not available 12.5 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria 12.6 Other adverse effects: Not described

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods: 13.1

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste:

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

Non-applicable

Non-applicable

Non-applicable

Non-applicable

see section 9

No

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- 14.1 UN number:
- Non-applicable UN proper shipping name: 14.2 Non-applicable
- Transport hazard class(es): 14.3
- Labels:
- 14.4 Packing group:
- 14.5 Environmental hazards:
- 14.6 Special precautions for user Tunnel restriction code: Physico-Chemical properties:
- 14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the IBC Code:



490101150 - GLUSHU QUICK PREFIX ADHESIVE 150 ML



Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1 SECTION 14: TRANSPORT INFORMATION (continued) Transport of dangerous goods by sea: With regard to IMDG 40-20: 14.1 UN number: Non-applicable 14.2 UN proper shipping name: Non-applicable 14.3 Transport hazard class(es): Non-applicable Labels: Non-applicable 14.4 Packing group: Non-applicable 14.5 Marine pollutant: No 14.6 Special precautions for user Special regulations: Non-applicable EmS Codes: Physico-Chemical properties: see section 9 Limited quantities: Non-applicable Segregation group: Non-applicable 14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the IBC Code: Transport of dangerous goods by air: With regard to IATA/ICAO 2023: 14.1 UN number: Non-applicable 14.2 UN proper shipping name: Non-applicable 14.3 Transport hazard class(es): Non-applicable Non-applicable Labels: Non-applicable 14.4 Packing group: 14.5 Environmental hazards: No 14.6 Special precautions for user Physico-Chemical properties: see section 9 Transport in bulk according to Non-applicable 14.7 Annex II of Marpol and the IBC

SECTION 15: REGULATORY INFORMATION

Code:

15.1	Safety, health and	environmental	regulations/legis	sla <mark>ti</mark> on spe <mark>c</mark> i	ific for the	substance	or mixture

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020. The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020. Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits.



490101150 - GLUSHU QUICK PREFIX ADHESIVE

150 ML



Printing: 01/10/2024 Date of compilation: 31/10/2023 Version: 1 **SECTION 16: OTHER INFORMATION** Legislation related to safety data sheets: This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H335: May cause respiratory irritation. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 **GB CLP Regulation:** Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H335 - May cause respiratory irritation. **Classification procedure:** Skin Irrit. 2: Calculation method STOT SE 3: Calculation method Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareneess or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.