According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Animal care product: Hoofpacking for horse hoof. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Glue-U Adhesives B.V. Droogdokkeneiland 8 5026 SR Tilburg - The Netherlands Phone: +31 (0)13 545 31 18

info@glue-u.com www.glue-u.com

1.4 Emergency telephone number: Medical Toxicology Unit, +44 20 7188 7188

SECTION 2: HAZARDS IDENTIFICATION

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Carc. 1B: Carcinogenicity, Category 1B, H350

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Danger



Hazard statements:

Carc. 1B: H350 - May cause cancer.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust

P308+P313: IF exposed or concerned: Get medical advice/attention.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

2.3 Other hazards:

Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane,

Octamethylcyclotetrasiloxane

Due to physical form (paste) classification with H372 is not appropriate. An inhalation of the product is not possible.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Silicone-based mixed solvent

Components:

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification		Concentration
CAS:	8042-47-5	White mineral oil, <=20.5mm2/s (40°C)		5 - <10 %
CAS.	0042-47-5	Asp. Tox. 1: H304 - Danger	③	3- < 10 /0
CAS:	14464 46 4	Cristobalite (RCS > 10 %)		5 - <10 %
CAS:	14464-46-1	STOT RE 1: H372 - Danger	③	3-<10 //
040	550.07.0	Octamethylcyclotetrasiloxane		<0.5 %
CAS:	556-67-2	Aquatic Chronic 4: H413; Flam. Liq. 3: H226; Repr. 2: H361 - Warning	♦	<0,5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

This product does not contain substances classified as hazardous for eye contact. Rinse eyes thoroughly for at least 15 minutes with lukewarm water, ensuring that the person affected does not rub or close their eyes.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 20 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:





250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

	Identification Occupational exposure limits		itional exposure limits
Cristobalite (RCS > 10 %)	WEL (8h) 0.1 mg/m³		
CAS: 14464-46-1		WEL (15 min)	

Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

DNEL (Workers):

	Short exposure Long exp		exposure		
Identification		Systemic	Local	Systemic	Local
White mineral oil, <=20.5mm2/s (40°C)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 8042-47-5	Dermal	Not relevant	Not relevant	217.05 mg/kg	Not relevant
EC: 232-455-8	Inhalation	Not relevant	Not relevant	164.56 mg/m ³	Not relevant
Octamethylcyclotetrasiloxane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 556-67-2	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 209-136-7	Inhalation	Not relevant	Not relevant	73 mg/m³	73 mg/m³

DNEL (General population):

		Short	exposure	posure Long exposure	
Identification		Systemic	Local	Systemic	Local
White mineral oil, <=20.5mm2/s (40°C)	Oral	Not relevant	Not relevant	25 mg/kg	Not relevant
CAS: 8042-47-5	Dermal	Not relevant	Not relevant	93.02 mg/kg	Not relevant
EC: 232-455-8	Inhalation	Not relevant	Not relevant	34.78 mg/m³	Not relevant
Octamethylcyclotetrasiloxane	Oral	Not relevant	Not relevant	3.7 mg/kg	Not relevant
CAS: 556-67-2	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 209-136-7	Inhalation	Not relevant	Not relevant	13 mg/m³	13 mg/m³

PNEC:

Identification				
Octamethylcyclotetrasiloxane	STP	10 mg/L	Fresh water	0.0015 mg/L
CAS: 556-67-2	Soil	0.54 mg/kg	Marine water	0.00015 mg/L
EC: 209-136-7	Intermittent	Not relevant	Sediment (Fresh water)	3 mg/kg
	Oral	0.041 g/kg	Sediment (Marine water)	0.3 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands



As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
**	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 1.5 % weight

V.O.C. density at 20 °C: 16.87 kg/m³ (16.87 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Solid

Paste

Paste

Characteristic

Not relevant *

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Not relevant *

Not relevant *

Not relevant *

Not relevant *

Product description:

Density at 20 °C: 1124.3 kg/m³ Relative density at 20 °C: 1.124

Dynamic viscosity at 20 °C: 1400000 cP

*Not relevant due to the nature of the product, not providing information property of its hazards.





250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: >20.5 mm²/s Not relevant 3 Concentration: pH: Not relevant * Vapour density at 20 °C: Not relevant * Not relevant * Partition coefficient n-octanol/water 20 °C: Solubility in water at 20 °C: Not relevant * Not relevant * Solubility properties: >180 °C Decomposition temperature: Not relevant * Melting point/freezing point: Flammability: >100 °C Flash Point: Flammability (solid, gas): Not relevant * >400 °C Autoignition temperature: Lower flammability limit: Not relevant * Upper flammability limit: Not relevant * **Explosive (Solid):** Not relevant * Lower explosive limit: Not relevant * Upper explosive limit: Particle characteristics: Median equivalent diameter: Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

Not relevant *

components:
Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant *

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability. Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
 - IARC: White mineral oil, <=20.5mm2/s (40°C) (3); Cristobalite (RCS > 10 %) (1)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.





250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Not relevant

Product-specific toxicological information:

	Acute toxicity	Genus
LD50 oral	>5000 mg/kg	Rat

Specific toxicology information on the substances:

Identification	Ac	Acute toxicity	
White mineral oil, <=20.5mm2/s (40°C)	LD50 oral	>5000 mg/kg	Rat
CAS: 8042-47-5	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Cristobalite (RCS > 10 %)	LD50 oral	>5000 mg/kg	
CAS: 14464-46-1	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Octamethylcyclotetrasiloxane	LD50 oral	61440 mg/kg	Rat
CAS: 556-67-2	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Dermal	>5000 mg/kg (Calculation method)	Non-applicable	
Inhalation	>5 mg/L (4 h) (Calculation method)	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Octamethylcyclotetrasiloxane	LC50	500 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 556-67-2	EC50	Not relevant		
	EC50	Not relevant		

Chronic toxicity:

Identification	Identification		Species	Genus
Octamethylcyclotetrasiloxane	NOEC	0.0044 mg/L	Oncorhynchus mykiss	Fish
CAS: 556-67-2		0.015 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Identification Bioaccumulation potentia	
Octamethylcyclotetrasiloxane	BCF	12400
CAS: 556-67-2	Pow Log	4.45
	Potential	Very High

12.4 Mobility in soil:

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Octamethylcyclotetrasiloxane	Koc	Not relevant	Henry	Not relevant
CAS: 556-67-2	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.819E-2 N/m (25 °C)	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane, Octamethylcyclotetrasiloxane

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class
Γ	16 05 08*	discarded organic chemicals consisting of or containing hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

14.5 Environmental hazards: No

14.6 Special precautions for user

Tunnel restriction code: Not relevant Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Not relevant Annex II of Marpol and the IBC

Code:

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: Not relevant 14.2 UN proper shipping name: Not relevant 14.3 Transport hazard class(es): Not relevant Labels: Not relevant 14.4 Packing group: Not relevant

14.5 Marine pollutant: Nο

14.6 Special precautions for user

> Not relevant Special regulations:

EmS Codes:

Physico-Chemical properties: see section 9 Limited quantities: Not relevant Not relevant Segregation group: Transport in bulk according to Not relevant 14.7

Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

14.1 UN number: Not relevant Not relevant 14.2 UN proper shipping name: 14.3 Transport hazard class(es): Not relevant Labels: Not relevant 14.4 Packing group: Not relevant No

14.5 **Environmental hazards:**

14.6 Special precautions for user

> Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Not relevant Annex II of Marpol and the IBC

Code:

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Octamethylcyclotetrasiloxane (556-67-2)
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Contains Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane, Dodecamethylcyclohexasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application." Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

According to UK REACH (S.I. 2019/758)



250106660/250106025 - SHUDIM SOFT A25 (B) 660 KG/2.5 KG



Printing: 18/11/2024 Date of compilation: 24/05/2023 Revised: 08/06/2023 Version: 8 (Replaced 7)

SECTION 16: OTHER INFORMATION (continued)

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H350: May cause cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

adhesives

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.