# according to 29 CFR 1910.1200

# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR

Safety data sheet



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# **SECTION 1: IDENTIFICATION**

**1.1 GHS Product identifier:** 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR

Other means of identification:

Not applicable (N/A)

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses: Zoosanitary product for animal care. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Glue-U Adhesives B.V. Droogdokkeneiland 8

5026 SR Tilburg - The Netherlands Phone: +31 (0)13 545 31 18

info@glue-u.com

www.glue-u.com

1.4 Emergency phone number: +31 (0)6 24533395 Mon-Fri 08-17

# SECTION 2: HAZARD(S) IDENTIFICATION

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

2.1 Classification of the substance or mixture:

#### NFPA:

Health Hazards: 0 Flammability Hazards: 1 Instability Hazards: 0

Special Hazards: Not applicable (N/A)

#### 29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Carc. 1B: Carcinogenicity, Category 1B, H350

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

# 2.2 Label elements:

#### NFPA:



#### 29 CFR 1910.1200:

#### Danger



#### **Hazard statements:**

Carc. 1B: H350 - May cause cancer.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust

P308+P313: IF exposed or concerned: Get medical advice/attention.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

### 2.3 Hazards not otherwise classified (HNOC):

Due to physical form (paste) classification with H372 is not appropriate. An inhalation of the product is not possible.



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances:

Non-applicable

#### 3.2 Mixtures:

Chemical description: Silicone-based mixed solvent

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

	Identification	Chemical name	Concentration
CAS:	8042-47-5	White mineral oil, <=20.5mm2/s (40°C)	5 - <10 %
CAS:	14464-46-1	Cristobalite (RCS > 10 %)	5 - <10 %
CAS:	556-67-2	Octamethylcyclotetrasiloxane	<0,5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

# **SECTION 4: FIRST-AID MEASURES**

#### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

This product does not contain substances classified as hazardous for eye contact. Rinse eyes thoroughly for at least 15 minutes with lukewarm water, ensuring that the person affected does not rub or close their eyes.

# By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

# **SECTION 5: FIRE-FIGHTING MEASURES**

# 5.1 Suitable (and unsuitable) extinguishing media:

# Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

# olue-u

# Safety data sheet according to 29 CFR 1910.1200

# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 5: FIRE-FIGHTING MEASURES (continued)

# 5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

# 5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

#### Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

# 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### 6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

#### 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, manipulation and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F
Maximum Temp.: 68 °F
Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

# 7.3 Specific end use(s):



250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification Occupational exposure limits		nal exposure limits
Cristobalite (RCS > 10 %)	8-hour TWA PEL	0.5 mg/m <sup>3</sup>
CAS: 14464-46-1	Ceiling Values - TWA PEL	

# CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupation	Occupational exposure limits		
Cristobalite (RCS > 10 %)	PEL	0.05 mg/m <sup>3</sup>		
CAS: 14464-46-1	STEL			

Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

#### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

# B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract	Filter mask for gases and vapours (Filter type:	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

#### C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 30 min, Thickness: 0.38 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

# D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions.  Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

#### E.- Bodily protection



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

# F.- Additional emergency measures

Emergency m	neasure	Standards	Emergency measure	Standards
<b>*</b>		ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>*</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency	shower		Eyewash stations	

# **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

# 40 CFR Part 59 (VOC):

# California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

# South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

# Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight 
V.O.C. at 68 °F: 0 kg/m³ (0 g/L)

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical prope	erties:
	For complete information see the product datasheet.	
	Appearance:	
	Physical state at 68 °F:	Solid
	Appearance:	Paste
	Color:	White
	Odor:	Characteristic
	Odour threshold:	Not applicable (N/A) *
	Volatility:	
	Boiling point at atmospheric pressure:	Not applicable (N/A) *
	Vapour pressure at 68 °F:	1000 Pa
	Vapour pressure at 122 °F:	Not applicable (N/A) *
	Evaporation rate at 68 °F:	Not applicable (N/A) *
	Product description:	
	*Not applicable (N/A) due to the nature of the product, not provide	ling information property of its hazards.



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Density at 68 °F: 1124.3 kg/m³

Relative density at 68 °F: 1.124

Dynamic viscosity at 68 °F: 1400000 cP

Kinematic viscosity at 68 °F: Not applicable (N/A) \*

Kinematic viscosity at 104 °F: >20.5 mm²/s

Concentration:

pH:

Not applicable (N/A) \*

Not applicable (N/A) \*

Vapour density at 68 °F:

Partition coefficient n-octanol/water 68 °F:

Solubility in water at 68 °F:

Not applicable (N/A) \*

Not applicable (N/A) \*

Not applicable (N/A) \*

Not applicable (N/A) \*

Decomposition temperature: >356 °F

Melting point/freezing point:

Not applicable (N/A) \*

Flammability:

Flash Point: >212 °F

Flammability (solid, gas): Not applicable (N/A) \*

Autoignition temperature: >752 °F

Lower flammability limit:

Upper flammability limit:

Not applicable (N/A) \*

Not applicable (N/A) \*

Explosive (Solid):

Lower explosive limit:

Upper explosive limit:

Not applicable (N/A) \*

Not applicable (N/A) \*

Particle characteristics:

Median equivalent diameter: Not applicable (N/A) \*

# 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties: Not applicable (N/A) \*

Oxidising properties:

Not applicable (N/A) \*

Not applicable (N/A) \*

Heat of combustion: Not applicable (N/A) \*

Aerosols-total percentage (by mass) of flammable Not applicable (N/A) \* components:

Other safety characteristics:

Surface tension at 68 °F:

Not applicable (N/A) \*

Refraction index:

Not applicable (N/A) \*

\*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

# **SECTION 10: STABILITY AND REACTIVITY**

# 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

# 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 10: STABILITY AND REACTIVITY (continued)

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
  - IARC: White mineral oil, <=20.5mm2/s (40°C) (3); Cristobalite (RCS > 10 %) (1)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Not applicable (N/A)

# Specific toxicology information on the substances:

Identification	Acu	te toxicity	Genus
White mineral oil, <=20.5mm2/s (40°C)	LD50 oral	>5000 mg/kg	Rat
CAS: 8042-47-5	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Cristobalite (RCS > 10 %)	LD50 oral	>5000 mg/kg	
CAS: 14464-46-1	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Octamethylcyclotetrasiloxane	LD50 oral	61440 mg/kg	Rat
CAS: 556-67-2	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

# Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Oral	>5000 mg/kg (Calculation method)	Non-applicable	
Dermal	>5000 mg/kg (Calculation method)	Non-applicable	
Inhalation	>5 mg/L (4 h) (Calculation method)	Non-applicable	

# **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect.

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

# 12.1 Ecotoxicity (aquatic and terrestrial, where available):

# Acute toxicity:

Identification		Concentration	Species	Genus
Octamethylcyclotetrasiloxane	LC50	500 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 556-67-2	EC50	Not applicable (N/A)		
	EC50	Not applicable (N/A)		

# Chronic toxicity:

Identification		Concentration	Species	Genus
Octamethylcyclotetrasiloxane	NOEC	0.0044 mg/L	Oncorhynchus mykiss	Fish
CAS: 556-67-2	NOEC	0.015 mg/L	Daphnia magna	Crustacean

#### 12.2 Persistence and degradability:

Not available

# 12.3 Bioaccumulative potential:

Substance-specific information:

# QUE-U adhesives

Printing: 11/18/2024

# Safety data sheet according to 29 CFR 1910.1200

•

Version: 8 (Replaced 7)



250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR

#### SECTION 12: ECOLOGICAL INFORMATION (continued) Identification Bioaccumulation potential BCF 12400 Octamethylcyclotetrasiloxane Pow Log 4 45 CAS: 556-67-2 Potential Very High Mobility in soil: Identification Absorption/desorption Volatility Not applicable (N/A) Not applicable (N/A) Octamethylcyclotetrasiloxane Henry Koc Not applicable (N/A) CAS: 556-67-2 Conclusion Not applicable (N/A) Drv soil 1.819E-2 N/m (77 °F) Surface tension Moist soil Not applicable (N/A)

Revised: 6/8/2023

#### 12.5 Results of PBT and vPvB assessment:

Non-applicable

#### 12.6 Other adverse effects:

Not described

# **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1 Disposal methods:

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

#### Waste management (disposal and evaluation):

Date of compilation: 5/24/2023

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

# Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

# **SECTION 14: TRANSPORT INFORMATION**

# Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:

14.1 UN number: Not applicable (N/A)
 14.2 UN proper shipping name: Not applicable (N/A)
 14.3 Transport hazard class(es): Not applicable (N/A)
 Labels: Not applicable (N/A)
 14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9


14.7 Transport in bulk (according to Not applicable (N/A)
Annex II of MARPOL 73/78 and

the IBC Code):

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

# Safety data sheet



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: Not applicable (N/A)
 14.2 UN proper shipping name: Not applicable (N/A)
 14.3 Transport hazard class(es): Not applicable (N/A)
 Labels: Not applicable (N/A)
 14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection

with transport or conveyance either within or outside their premises

Special regulations: Not applicable (N/A)

EmS Codes:

Physico-Chemical properties: see section 9
Limited quantities: Not applicable (N/A)
Segregation group: Not applicable (N/A)

14.7 Transport in bulk (according to Not applicable (N/A)

Annex II of MARPOL 73/78 and

the IBC Code):

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

14.1 UN number: Not applicable (N/A)
 14.2 UN proper shipping name: Not applicable (N/A)
 14.3 Transport hazard class(es): Not applicable (N/A)
 Labels: Not applicable (N/A)
 14.4 Packing group, if applicable: Not applicable (N/A)

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises.

with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

Transport in bulk (according to Not applicable (N/A)

Annex II of MARPOL 73/78 and

the IBC Code):

14.7

# **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE The Hazardous Substances List: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Birth defects or other reproductive harm: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Cancer: Not applicable (N/A)
- CANADA-Domestic Substances List (DSL): White mineral oil, <=20.5mm2/s (40°C) (8042-47-5); Cristobalite (RCS > 10 %) (14464-46-1); Octamethylcyclotetrasiloxane (556-67-2)
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantities: Not applicable (N/A)
- Hazardous Air Pollutants (Clean Air Act): Not applicable (N/A)
- Massachusetts RTK Substance List: *Cristobalite (RCS > 10 %) (14464-46-1)*
- Minnesota Hazardous substances ERTK: Cristobalite (RCS > 10 %) (14464-46-1)
- New Jersey Worker and Community Right-to-Know Act: Cristobalite (RCS > 10 %) (14464-46-1)
- New York RTK Substance list: Not applicable (N/A)
- NTP (National Toxicology Program): Cristobalite (RCS > 10 %) (14464-46-1)
- OSHÀ Specifically Regulated Substances (29 CFR 1910.1001-1096): Cristobalite (RCS > 10 %) (14464-46-1)
- Pennsylvania Worker and Community Right-to-Know Law: Cristobalite (RCS > 10 %) (14464-46-1)
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: Cristobalite (RCS > 10 %) (14464-46-1); Octamethylcyclotetrasiloxane (556-67-2)
- Rhode Island Hazardous substances RTK: Not applicable (N/A)
- The Toxic Substances Control Act (TSCA): White mineral oil, <=20.5mm2/s (40°C) (8042-47-5); Cristobalite (RCS > 10 %) (14464-46-1); Octamethylcyclotetrasiloxane (556-67-2)
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Not applicable (N/A)

Specific provisions in terms of protecting people or the environment:



# 250105025/250105660 - SHUDIM SUPER SOFT A15 (B) 2.5 KG/660 GR



Printing: 11/18/2024 Date of compilation: 5/24/2023 Revised: 6/8/2023 Version: 8 (Replaced 7)

# SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

# Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

# **SECTION 16: OTHER INFORMATION**

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

#### Texts of the legislative phrases mentioned in section 2:

H350: May cause cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

# Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

#### Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

#### Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 5/24/2023

Revised: 6/8/2023

adhesives

Manufacturer Disclaimer: The information contained in this safety date sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).